

AMENDMENTS TO THE CLAIMS

1. (Withdrawn) A storm water detention system comprising a basin sized and positioned to accumulate storm water, an outlet, and a flow limiting structure impeding flow of water out of the basin through the outlet, the flow limiting inlet structure comprising:

a set of two or more baffles adapted to hinder floating surface contaminants into the outlet;

a discharge riser having openings sized or spaced such that a discharge flow rate remains substantially independent of the water depth;

wherein each of the baffles has an upper edge and a lower edge;

the upper edge defines an upper opening;

the lower edge defines a lower opening; and

wherein each baffle is coupled to the riser such that water is able to flow over the upper edge into the riser through the upper opening.

2. (Withdrawn) The system of claim 1 wherein the set of two or more baffles are a tiered set of nested baffles wherein:

each baffle that is nested within another baffle is positioned at a lower height than the baffle it is nested within;

the baffles of the set of baffles overlap each other;

the difference in height between the upper edge of any baffle that is nested within another baffle and the lower edge of the baffle it is nested within is at least 1/2 inch; and

wherein the baffles have relative spacing such that the discharge rate remains substantially independent of the water depth.

3. (Cancelled)
4. (Currently Amended) A flow limiting inlet structure comprising a discharge riser incorporating a plurality of holes thereon wherein the riser is surrounded by a tiered set of nested baffles wherein an inlet area created by the nested baffles increases as fluid depth increases, and at least one of the set of nested baffles having an upper edge defining an upper opening allowing water to flow through and into the holes then subsequently into ~~discharge riser and subsequently into the holes disposed on the riser.~~
5. (Original) The structure of claim 4 wherein each baffle that is nested within another baffle is positioned at a lower height than the baffle it is nested within.
6. (Cancelled)
7. (Previously Presented) The structure of claim 4 wherein the difference in height between the upper edge of any baffle that is nested within another baffle and a lower edge of the baffle it is nested within is at least 1/2 inch.
8. (Cancelled)
9. (Cancelled)
10. (Cancelled)
11. (Original) The structure of claim 4 wherein the number of baffles in the set of baffles is at least X where X is one of 2, 3, and 4.
12. (Previously Presented) The structure of claim 4 wherein each baffle is sized or configured such that a discharge rate through an outlet remains substantially independent of the water depth.
13. (Cancelled)
14. (Cancelled)
15. (Cancelled)